

TECHNICAL DATA OF RV-HWD-1200(102323)

Feature:

- 1.Safe and Durable.
- 2.High tensile, tear and ahesion strength.
- 3.Excellent ability on Waterproof, anti-UV, fire retardant, mouldproofing, antiabrasion and self-cleaning for option
- 4.Good resilience, Outstanding opacity.
- 5.Ideal for inflatable boat, swimming pool liner, tent, truck cover, side curtain,high-ends projects, mega marquees, or mobile constructions at harsh conditions.

Specification:

Base fabric	1000Dx1000D 23x23/sq.yd 1100dtex x1100dtex 9x9/sq.cm	DIN 53830/DIN60001 ASTM D 751
Weight/Thickness	1200gsm+/- 50gsm 0.9mm	DIN53352
Lacquering	35oz	ASTM D 751
Breaking strength (Warp/weft)	3100/2500N/5cm 706lbs/570lbs/2"	DIN 53354 FS 5100
Tearing strength	483/421N/5cm 110lbs/96lbs	DIN 53363 FS 5100
Adhesion strength	120N/5cm 27lbs/2"	DIN 53357 FS 5970
Avilable width	1000-3200mm 36"-126"	
Fire retardant	M2, B1, NFPA 701, B2	
Temperature resistance	- 30°C ~ 70°C - 20°F ~ 158°F	DIN 53372 FS 5874

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.



HANGZHOU REEVOO INDUSTRY CO., LTD.

Add.:No.159-4 Fengpu Road, Fuyang District,
Hangzhou, Zhejiang, China. P.C.:311400
Tel:+86-571-23281868 Fax:+86-571-23281899
Email:reevoo@reevoo.net.cn
Http://www.reevooindustrial.com